

Issue Date: April 9, 2015

Revision Date: April 9, 2015

Version: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Arisfor® Patch Kit - Cementitious Powder Component

Recommended Use: Concrete Damp-proofing Coating
Restrictions on Use: No Data

Supplier of the Safety Data Sheet including Address:

Arisfor, LLC
100 Forta Drive
Grove City, PA 16127

Telephone Numbers

Company Phone Number

Phone: 724-264-1050

Fax: 724-458-8331

Emergency Telephone: 724-264-1050

2. HAZARDS IDENTIFICATION

Emergency Overview

OSHA Hazards:

Harmful if swallowed. Causes severe skin burns and eye damage. Harmful if inhaled. Suspected of causing cancer by inhalation of respirable crystalline silica. Causes damage to Lungs through prolonged or repeated exposure by inhalation.

Target Organs: Lungs

GHS Classification:

Acute Toxicity Oral – Category 4

Carcinogenicity – Category 2

Eye damage/eye irritation – Category 1

Skin sensitization – Category 1

Skin irritation – Category 1

Specific target organ toxicity – repeated exposure – Category 2, Respiratory System

Label Elements, including precautionary statements

Pictograms:



Signal Word: DANGER

Hazard Statements:

- H302 Harmful if swallowed
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary Statement(s)

Prevention:

- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P264 Wash hands and skin thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response:

- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P310 Immediately call a POISON CENTER/doctor.
- P303+P313+P310 IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with plenty of water or shower. Immediately call a POISON CENTER/doctor.
- P363 Wash contaminated clothing before reuse.
- P333+P313 If skin irritation or rash occurs: Get medical advice or attention.
- P304+P340+P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P314 Repeated Exposure: Get medical advice/attention if you feel unwell.

Storage:

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Disposal:

- P501 Dispose of contents/container in accordance with local/regional/national regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component

Cement	CAS#: 65997-15-1	20-30%
Crystalline Silica in the form of Quartz	CAS#: 14808-60-7	60-70%
Calcium Magnesium Hydroxide	CAS#: 39445-23-3	1-5%
Additives	Proprietary	≤0.2%
Various Pigments Including:		0.1-5%
Titanium Dioxide, CAS#: 13463-67-7		
Iron Oxide Blends: CAS#: Various (Non-Hazardous)		

Ingredients not listed on this safety data sheet are considered to be non-hazardous according to OSHA 1910.1200 or are not present above their cutoff levels. Where a range is displayed, the exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First Aid Measures

General Advice: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

Inhalation: If breathed in, move person into fresh air and keep comfortable for breathing. Consult a physician.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult a physician.

Ingestion: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Skin Contact: Remove contaminated clothing. Wash off with soap and plenty of water. Consult a physician.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Material is Non-combustible. Use Water spray, alcohol-resistant foam, dry chemical, or carbon dioxide for surrounding fire.

Specific Hazards Arising from the Chemical

Avoid breathing dust. Wet cement is caustic.

Hazardous Combustion Products

Calcium Oxide, Sulfur Dioxide

Protective Equipment and Precautions for Firefighters

Wear self-contained breathing apparatus and full protective gear for firefighting.

Further Information: See Section 7 for safe handling and storage.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Avoid actions that cause the material to become airborne. Avoid inhalation of dust and contact with skin. Wear appropriate personal protective equipment during any cleanup and response activities.

Environmental Precautions

Do not wash cement down sewage and drainage systems or into bodies of water.

Methods and Material for Containment and Cleaning Up

Place spilled material into a container. Scrape wet material and place in container. Allow material to dry or solidify before disposal. Dispose of cement according to Federal, State, Provincial and Local regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Conditions for Safe Storage, Including any Incompatibilities

General information: Keep bagged material dry until used. Stack bagged material in a secure manner to prevent falling. Bagged material is heavy and poses risks such as sprains and strains to the back, arms, shoulders and legs during lifting and mixing. Handle with care and use appropriate control measures.

Incompatibilities: Water will cause product to solidify.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Component Exposure Limits

Cement CAS#: 65997-15-1 OSHA 15 mg/m³ T (Total) / 5 mg/m³ R (Respirable)

Silica, Quartz CAS#: 14808-60-7 OSHA TWA 10 mg/m³, ACGIH TWA 0.025 mg/m³

Calcium Magnesium Hydroxide Hydrated CAS#: 39445-23-3 OSHA TLV 5 mg/m³

Appropriate Engineering Controls

Local Ventilation: Recommended

General Ventilation: Recommended

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection: Use proper protection – Safety Glasses as a minimum

Skin and Body Protection: Wash at mealtime and end of shift. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc.). Use chemical protective gloves as a minimum and wash skin promptly upon any skin contact.

Respiratory Protection: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Wash hands before & after breaks and work day.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State

Appearance: Solid Powder

Color: Various Colors, Including White & Gray

Odor: Mild

Odor threshold: No Data

<u>Property</u>	<u>Value</u>	<u>Remarks – Method</u>
Vapor Pressure	Not Available	
Vapor Density	Not Available	
Relative Density	Not Available	
pH (In Water)	12-13	
Melting/Freezing Point	Not Relevant	
Solubility	Not Available	
Evaporation Rate	Not Available	
Flash Point	Not Relevant	
Flammability Limits	Not Available	
Flammability (Solid, gas)	Not Relevant	
Auto Ignition Temperature	Not Available	
Initial Boiling Point/Boiling Range	Not Available	
Decomposition Temperature	Not Available	
Viscosity	Not Available	
Specific Gravity	Not Available	

STABILITY AND REACTIVITY

Chemical Stability:

Stable.

Possibility of Hazardous Reactions:

Hazardous polymerization will not occur.

Conditions to Avoid:

Keep dry until use. Avoid contact with incompatible materials.

Incompatible Materials:

Wet cement is alkaline and is incompatible with acids, ammonium salts and aluminum metal. Cement dissolves in hydrofluoric acid, producing corrosive silicon tetrafluoride gas. Cement reacts with water to form silicates and calcium hydroxide. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.

Hazardous Decomposition Products

None known

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Inhalation, Skin Contact, Eye Contact, Ingestion

Symptoms of Exposure:

Inhalation: May cause respiratory irritation

Skin: Causes severe skin burns. May cause allergic skin reaction.

Eyes: Causes serious eye damage

Ingestion: Irritation of the digestive system may occur if large amounts are swallowed.

Numerical measures of toxicity:

Acute Toxicity Value: Silica-LD50 oral rat 22,500 mg/kg

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-Term Exposure

Dermatitis:

Irritant Dermatitis is caused by physical properties of cement including alkalinity and abrasion. **Allergic Dermatitis** is caused by sensitization to hexavalent chromium (Chromate) present in cement. The reaction can range from a mild rash to severe skin ulcers. Persons already sensitized may react to the first contact with cement. Others may develop allergic dermatitis after years of repeated contact with cement.

Carcinogenicity:

IARC: 1-Group 1: Carcinogenic to humans (Quartz)

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: Carcinogenic to humans (Quartz)

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Specific target organ toxicity: Single exposure – No data available.

Specific target organ toxicity: Repeated exposure – Category 2, Respiratory System.

Silicosis: Silicosis is caused by the inhalation and retention of respirable crystalline silica dust.

Simple Chronic Silicosis - results from long-term exposure (more than 20 years) to low amounts of respirable crystalline silica. Nodules of chronic inflammation and scarring provoked by the respirable crystalline silica form in the lungs and chest lymph nodes. This disease may feature breathlessness and may resemble chronic obstructive pulmonary disease (COPD).

Accelerated silicosis – occurs after exposure to larger amounts of respirable crystalline silica over a shorter period of time (5-15 years). Inflammation, scarring, and symptoms progress faster in accelerated silicosis than in simple silicosis.

Acute silicosis – results from short-term exposure to very large amounts of respirable crystalline silica. The lungs become very inflamed and may fill with fluid, causing severe shortness of breath and low blood oxygen levels.

Pre-Existing Conditions: Cement dust is irritating to the nose, throat and respiratory tract causing coughing and sneezing. Pre-existing upper respiratory and lung diseases including asthma and bronchitis may be aggravated.

12. ECOLOGICAL INFORMATION

Eco toxicity: Not expected to be hazardous to the environment.

Persistence and Degradability: No Data Available

Bioaccumulation: No Data Available

Mobility: No Data Available

Other Adverse Effects: No Data Available

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes: This product is not expected to be a hazardous waste under RCRA. Place spilled material into a container. Scrape wet material and place in container. Allow material to dry or solidify before disposal. Dispose of according to Federal, State, Provincial and Local regulations.

Contaminated Packaging: Dispose of as unused material.

14. TRANSPORT INFORMATION

DOT: Not a Dangerous Good

IATA: Not a Dangerous Good

IMDG: Not a Dangerous Good

Marine Pollutant: No

15. REGULATORY INFORMATION

International Inventories

TSCA: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

US Federal Regulations

SARA 302: None Known

SARA 311/312 Hazard Categories: Acute Health Hazard, Chronic Health Hazard

SARA 313 Hazard Categories: None Known

CWA (Clean Water Act): None Known

Supplemental State Compliance Information

California:

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

Quartz CAS#:14808-60-7
Hexavalent Chromium Compounds

New Jersey Right TO Know
CAS Number Component Name
14808-60-7 Quartz

Pennsylvania Right To Know
CAS Number Component Name
14808-60-7 Quartz

Massachusetts Right To Know
CAS Number Component Name
14808-60-7 Quartz

U.S. EPA Label Information: No Data

Canada

WHMIS Classification: Class D2B (Toxic) & Class E (Corrosive)

Symbol: Stylized T, Corrosive



16. OTHER INFORMATION

HMIS Classification:

Health hazard: 2
Flammability: 0
Physical Hazards: 0

NFPA Rating:

Health hazard: 2
Fire: 0
Reactivity Hazard: 0

Issue Date: April 9, 2015

Revision Date: April 9, 2015

Version: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Arisfor® Patch Kit - Liquid Bond Component

Recommended Use: High Solids Acrylic Latex Bonding Agent and Admixture
Restrictions on Use: No Data

Supplier of the Safety Data Sheet including Address:

Arisfor, LLC
100 Forta Drive
Grove City, PA 16127

Telephone Numbers

Company Phone Number

Phone: 724-264-1050
Fax: 724-458-8331

Emergency Telephone: 724-264-1050

2. HAZARDS IDENTIFICATION

Emergency Overview

OSHA Hazards:

Causes eye irritation, May be harmful if swallowed, May cause an allergic skin reaction, May cause skin irritation.

GHS Classification:

Eye damage/irritation – Category 2B
Acute Toxicity – Oral – Category 5
Sensitization – Skin – Category 1A

Label Elements, including precautionary statements

Pictograms:



Signal Word: Warning

Hazard Statements:

H303 May be harmful if swallowed.
H320 Causes eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

Precautionary Statement(s)

Prevention:

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash hands and skin thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response:

- P312 Call a POISON CENTER/doctor if swallowed and you feel unwell.
- P304+P340+P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313 If eye irritation persists: Get medical advice or attention.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P333+P313 If skin irritation or rash occurs: Get medical advice or attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.

Storage:

- P405 Store locked up.

Disposal:

- P501 Dispose of contents/container in accordance with local/regional/national regulations.

Hazards not otherwise classified: May cause skin irritation.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component

Water	CAS#: 7732-18-5	70-75%
Latex Resin – Non Hazardous	CAS#: Not Available	20-25%
S-Triazine-1,3,5(2H,4H,6H)-Triethanol	CAS#: 4719-04-4	≤ 0.3%
Surfactant Blend	Proprietary	≤ 0.2%

Ingredients not listed on this safety data sheet are considered to be non-hazardous according to OSHA 1910.1200 or are not present above their cutoff levels. Where a range is displayed, the exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First Aid Measures

General Advice: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

Inhalation: IF INHALED: Call a POISON CENTER/doctor if you feel unwell.

Eye Contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Ingestion: IF SWALLOWED: Not expected to be harmful under normal conditions of use. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Call a POISON CENTER/doctor if you feel unwell.

Skin Contact: Wash off with plenty of soap and water. If skin irritation or rash occurs: Get medical advice or attention.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Material is not combustible. Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide for the surrounding fire.

Specific Hazards Arising from the Chemical

No specific data available.

Hazardous Combustion Products

No specific data available.

Protective Equipment and Precautions for Firefighters

Wear self-contained breathing apparatus and full protective gear for firefighting.

Further Information

See Section 7 for safe handling and storage.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

In case of spill wear appropriate personal protective equipment during any cleanup and response activities. Avoid skin contact and inhalation.

Environmental Precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods and Material for Containment and Cleaning Up

Dike and contain spill with inert absorbent materials. Soak up with inert material and keep in suitable, closed containers for disposal. Dispose of in accordance with specified local/regional/national/international regulations for disposal.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Conditions for Safe Storage, Including any Incompatibilities

General information: Keep container tightly closed in a dry and well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep away from heat. Keep from freezing. Store product above 50 degrees F/10 degrees C and below 95 degrees F/35 degrees C.

Safe Storage: No Additional Data

Incompatibilities: None known

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Component Exposure Limits

No Data Available

Appropriate Engineering Controls

Local Ventilation: Recommended

General Ventilation: Recommended

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection: Use proper protection – Safety Glasses as a minimum

Skin and Body Protection: Wash at mealtime and end of shift. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc.). Use chemical protective gloves as a minimum and wash skin promptly upon any skin contact.

Respiratory Protection: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Wash hands before & after breaks and work day.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State

Appearance: Liquid

Odor: Mild

Color: White (Dries Clear)

Odor threshold: No Data

<u>Property</u>	<u>Value</u>	<u>Remarks – Method</u>
Vapor Pressure	Not Available	
Vapor Density	Not Available	
Relative Density	Not Available	
pH:	9	
Melting/Freezing Point	32 Degrees F (0 Degrees C)	
Solubility	Not Available	
Evaporation Rate	Not Available	
Flash Point	>212 Degrees F (>100 Degrees C)	Closed Cup
Flammability Limits	Not Relevant	
Flammability (Solid, gas)	Not Relevant	
Auto Ignition Temperature	Not Available	
Initial Boiling Point/Boiling Range	≥212 Degrees F (>100 Degrees C)	
Decomposition Temperature	Not Available	
Viscosity	Not Available	
Specific Gravity	1.03	Density: 8.61 lb./gal. +/- 0.02

10. STABILITY AND REACTIVITY

Chemical Stability: Stable

Possibility of Hazardous Reactions: None Known

Conditions to Avoid: Keep from Freezing

Incompatible Materials: None Known

Hazardous Decomposition Products: Oxides of Carbon, Sulphur and Nitrogen

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Skin Contact, Eye Contact
(Ingestion is not a likely route of exposure under normal conditions of use.)

Symptoms of Exposure:

Allergic skin reaction, skin and eye irritation, stomach or intestinal upset

Numerical measures of toxicity:

No Data Available

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-Term Exposure

May harmful if swallowed. May cause allergic skin reaction, skin and eye irritation

Carcinogenicity: No ingredient has been characterized as a potential carcinogen by either IARC, NTP or OSHA.

12. ECOLOGICAL INFORMATION

Eco toxicity: No Known significant effects or critical hazards.

Persistence and Degradability: No Data Available

Bioaccumulation: No Data Available

Mobility: No Data Available

Other Adverse Effects: No Known significant effects or critical hazards.

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes: This product is a not a hazardous waste under RCRA. Dispose of in conformance with all federal, state and local regulations.

Contaminated Packaging: Dispose of as unused material.

14. TRANSPORT INFORMATION

DOT: Not Regulated

IMDG: Not Regulated
Marine Pollutant: No

IATA: Not Regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

US Federal Regulations

SARA 302: None Known

SARA 311/312 Hazard Categories: Acute Health Hazard

SARA 313 Hazard Categories: None Known

CWA (Clean Water Act): None Known

Supplemental State Compliance Information

California:

This product does not contain any chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

U.S. EPA Label Information: No Data

Canada

WHMIS Classification: Class D2B (Toxic)

Symbol: Stylized T



16. OTHER INFORMATION

HMIS Classification:

Health hazard: 1

Flammability: 0

Physical Hazards: 0

NFPA Rating:

Health hazard: 1

Fire: 0

Reactivity Hazard: 0